



## UK DECLARATION OF CONFORMITY

No. CPGRS001

1. Unique code of identification for each type of product:  
**Dry-pressed ceramic tiles, with water absorption H<sub>2</sub>O E ≤ 0,5%**
2. Destination of use:  
**Internal and external walls and floorings**
3. Name or trade mark and address of manufacturer:  
**CIPA GRES S.p.A.  
Via Statale 467, 119 - 42013 Casalgrande (RE) - Italia**
4. System of assessment and verification of constancy of performance (AVCP):  
**System 4**
5. Name and number of identification of laboratory notified, if applicable:  
**Not Applicable**
6. Declared performance:

Essential characteristics	Performance	Harmonized technical Specification
Fire Resistance	A1 <sub>FL</sub> /A1	BS EN 14411:2012
Release of dangerous substances, for:		
▪ Cadmium	npd	
▪ Lead	npd	
Breaking Strength	Thickness < 7,5mm Breaking strength ≥ 700 N	
	Thickness ≥ 7,5mm Breaking strength ≥ 1300 N	
Tactility	npd	
Slip Resistance	ndp	
Bond Strength for:		
▪ Adhesion cement, Type C2	npd	
Resistance to thermal shocks	Resistant	
Durability for:		
▪ Internal use	Resistant	
▪ External use: frost resistance	Resistant	

*The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.*

*Signed for and on behalf of the manufacturer by:*

Casalgrande, 07/11/2022

Giovanni Fiandri  
Chief Executive Officer  
**CIPA GRES SPA**  
Via Statale 467 n. 119  
42013 CASALGRANDE (RE) ITALY  
Tel. +39 0522 846890 Fax +39 0522 849910  
Partita IVA IT 01409620356  
Codice Fiscale 01880740368

UKCA-REV.N.0



## UKCA MARKING

Full Body Porcelain Tile

<b>UK CA</b>	
<b>CIPA GRES S.p.A.</b> Via Statale 467, 119 - 42013 Casalgrande (RE) - Italia  05  No. CPGRS001	
<b>BS EN 14411</b>  Dry pressed ceramic tiles, with water absorption $E \leq 0,5$ % for floors and internal /external walls	
Fire Resistance	A1 <sub>FL</sub> /A1
Release of dangerous substances, for:	
▪ Cadmium	npd
▪ Lead	npd
Breaking Strength	Thickness < 7,5mm Breaking Strength $\geq 700$ N
	Thickness $\geq 7,5$ mm Breaking Strength $\geq 1300$ N
Tactility	npd
Slip resistance	npd
Bond Strength for:	
▪ Adhesion Cement, Type C2	npd
Resistance to thermal shocks	Resistant
Durability for:	
▪ Internal Use	Resistant
▪ External Use: frost resistance	Resistant

UKCA-REV.N.0